

Lick

Safety data sheet.

PRODUCT DESCRIPTION

Lick Home Paint is a premium quality interior paint designed to provide a luxurious, self-priming finish in a durable 100% acrylic, low VOC formulation. Excellent for use on walls, trim and ceiling surfaces in residential and commercial applications. Lick Paint can be used on drywall, plaster, masonry, metal, wood and hardboard. Ideal for living rooms, bedrooms, offices, classrooms, standard doors/trim and much more.

PERFORMANCE FEATURES

AVAILABLE PRODUCTS

PRODUCT SPECIFICATIONS

FEATURES & SPECIFICATIONS

- Luxurious Appearance
- Low Spatter
- Mildew Resistant
- Very Low Odor & VOC
- Self-Priming
- Lifetime Warranty

MEETS VOC LIMITS

- ✓ CARB
- ✓ SCAQMD
- ✓ National AIM
- ✓ LEED v4
- ✓ GS-11

FINISHES:

Matt 10 @ 60°
Eggshell 35 @ 60°

SIZES: 1 Gallon

RESIN TYPE: 100% Acrylic

VOC (ASTM D6886): < 2 g/L

SOLIDS BY VOLUME:

Matt 36 ± 2%
Eggshell 37 ± 2%

WEIGHT PER GALLON:

Matt 10.6 ± .25 lbs.
Eggshell 10.4 ± .25 lbs.

SUBSTRATES & SYSTEM RECOMMENDATIONS

PREP: All surfaces must be cured, firm and dry. Use a suitable cleaner to remove all dirt, oil or other contamination. Sand glossy surfaces and remove dust. (See WARNING!)

PAINT: Coats – Lick Paint

Brush: Synthetic Bristle
Roll: 3/8"-3/4" Synthetic Cover
Spray: 2000-2500 PSI / .015"- .019" Tip
Thickness: 4-6 Mills Wet / 1.5-2.2 Mills Dry
Coverage: 250-400 sq/ft Per Gallon

Temperature: 50°F - 100°F
Dry Time: 2 Hours Touch / 4 Hours Recoat
Clean-up: Water
Thinning: Not Required / <10% Water, If Necessary

PAINT & PRIMER ALL-IN-ONE: This product is self-priming over properly prepared painted surfaces and bare drywall, wood, or masonry (<9 pH). Apply 1 coat as a primer with 1-2 additional topcoats. Allow at least 4 hours between all coats.

A specialty primer may be required in some situations such as significant color changes, porous substrates, dense or glossy surfaces, heavy tannins, or stains. If you have any questions contact us.

PREPARATION & APPLICATION

BEFORE PAINTING

GENERAL PREPARATION: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces. (See WARNING!)

NEW FERROUS METAL: Remove all loose rust, mill scale, or deteriorated previous coatings by Hand Tooling (SSPC-SP-2) or Power Tool Cleaning (SSPC-SP-3).

NEW ALUMINUM & GALVANIZED METAL: Wash surface with TSP or other suitable cleaner, degreaser, or etching solution to remove oil and contaminants. Rinse thoroughly.

TANNIN RICH WOOD: Allow to weather until tannins naturally come out of the substrate. Clean tannins from surface prior to priming and painting.

NEW & BARE SURFACES: Prime surfaces following recommendations on page 1 & 2.

PREVIOUSLY PAINTED SURFACES: Remove any peeling, chalky or loosely adhering paint, sand to feather edges, dust clean (do not use tack rags). Glossy surfaces should be completely dulled prior to painting. (See WARNING!) Spot prime bare and patched areas or prime entire surface. When making a significant color or sheen change, a primer is recommended to aid hide and appearance of the topcoat.

MOISTURE: All surfaces should be dry before painting. Wood should have an internal moisture content of less than 15%. Masonry and plaster should be thoroughly cured and have an internal moisture content of less than 12%.

STAIN BLOCKING: When painting over stains or tannins, an appropriate primer is recommended before top coating. For heavy stains, a second coat of primer may be required. 24 hours are required between all coats.

PATCHING & CAULKING: Prime the surface then apply paintable patching or siliconized acrylic caulking to the manufacturer's recommendations. Patching should be reprimed once dry. Caulking should be allowed to fully dry, then the finish paint applied. Using fast dry primers over caulking is not recommended. Elastomeric patch & caulking are recommended with elastomeric paints only. Painting over flexible patch or caulking or in areas with substrate movement may cause cracking of the topcoat.

MIXING: Mix well before use. Purchase enough paint to complete your project at the same time. If additional paint is needed, retain some of the original material and intermix the paint before application or touch up.

THINNING: Apply at can consistency. If thinning is necessary to maintain workability, do not exceed 10%.

CONTAINERS AND TOOLS: Transfer material into a clean container for use. Use new or thoroughly cleaned tools. To avoid contamination, do not re-dip applicators or add used material into containers being used for storage.

DURING PAINTING

GENERAL PAINTING: Apply two separate finish coats to create even color, uniform sheen, maximum durability and easier touch-up. Maintain a wet edge while painting.

TESTING: Prior to full application, apply a test patch to ensure the preparation and coating system are appropriate for the project. If test patch results do not meet the needs of the project, contact us

COVERAGE: May vary depending on method of application, porosity and texture of the surface.

FILM THICKNESS: Always follow recommendations for application thickness on page 1. Over application may reduce performance and can lead to runs, extended dry times or a soft film.

WEATHER: Apply product only when material, air, and surface temperature are within the recommendations on page 1 and will remain above that temperature for at least 24 hours. Temperatures must remain 5° above the dew point during application and dry time. Do not expose to rain, fog, snow or any moisture during application or dry time. Limit exposure to heavy moisture for 24-48 hours after application.

BACKROLLING: While spraying, follow with a wet roller to ensure an even coat and fill in porous surfaces. This will reduce pinholes, create uniform sheen and make for easier touch-up.

FIBER CEMENT BOARD: Prime bare or factory primed surfaces. A minimum of two finish coats are required for sheen uniformity and touch up. Backroll all spray applied coats for best results.

RECOATING: Always follow recommendations for recoat times on page 1. Recoating too soon or too long after painting may reduce performance and can lead to adhesion loss, improper cure or a soft film.

AFTER PAINTING

DRYING: Dry times are based on standard conditions of 75°F with a relative humidity of 50%. Lower temperatures or higher humidity may extend drying times. Higher temperatures may speed drying time. Provide adequate ventilation and air movement during and after painting.

STORAGE: Store material at room temperature in a clean, tightly sealed container free of rollers, brushes, or other outside materials. Protect from freezing.

CURE: Architectural paints require up to 30 days after final application for full cure and maximum performance. Cure times vary depending on environmental conditions and air circulation.

CLEANING: Wait until at least two weeks after final paint application. Clean with fresh water and a cotton cloth. A small amount of mild detergent can be used, if necessary.

SAFETY INFORMATION

CAUTION!

Harmful if inhaled. Causes eye, nose, throat and lung irritation. Overexposure may cause lung damage. Close container after each use. Keep away from heat and flame.

Do not breath dust, vapors or spray mist. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1- 800-424-LEAD (5323) or log on to www.epa.gov/lead.

Matt , Eggshell

WARNING Cancer and Reproductive Harm- www.P65Warnings.ca.gov/product



First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

DO NOT TAKE INTERNALLY
USE ONLY WITH ADEQUATE VENTILATION
KEEP OUT OF REACH OF CHILDREN

SEE THE SAFETY DATA SHEET (SDS) FOR ADDITIONAL HEALTH AND SAFETY INFORMATION

Subject to the limitations set forth in this Technical Data Sheet, Lick North America, Inc. ("LICK NORTH AMERICA ") warrants that the Lick Home Paint product (the "Product") shall be free from peeling, blistering and cracking defects during the Lifetime (as hereinafter defined) (the " Lifetime Limited Warranty"). This Lifetime Limited Warranty applies to and requires the painting of properly-prepared exterior surfaces with one (1) coat of the appropriate LICK NORTH AMERICA primer followed by two (2) separate coats of the Product by the owner ("Owner") or his/her/its contractor on the structure. For the purpose of this Lifetime Limited Warranty, the term "Lifetime" means and refers to that period commencing on the date of application of the Product on the structure until such time that the Owner conveys, assigns, sells or transfers the structure on which the Product has been applied (the "Warranty Period"). This Lifetime Limited Warranty is non-transferrable and non-assignable. All recommendations for surface preparation and application made on this Technical Data Sheet must be strictly followed in order for the Lifetime Limited Warranty to be valid. If LICK NORTH AMERICA verifies that the Product peels, blisters or cracks during the Warranty Period due to a defect of the Product, Owner's sole and exclusive remedy shall be LICK NORTH AMERICA 's replacement, at no additional cost to Owner, of an adequate quantity of the Product required to repair the affected portions of the subject surfaces to a sound condition. Owner shall not be entitled to any other remedy in lieu of Product replacement. LICK NORTH AMERICA does not warrant the film integrity of previously applied coatings. This Lifetime Limited Warranty does not apply to improperly prepared or below grade surfaces, surfaces not specifically recommended for coating application or coating failures resulting from cracks or openings, structural defects, faulty construction, physical abuse, extreme weather, natural disasters or other causes beyond LICK NORTH AMERICA 's reasonable control. Color fading is specifically excluded from this Lifetime Limited Warranty. This Lifetime Limited Warranty excludes labor and the cost of labor. No modifications, changes or amendments to this Lifetime Limited Warranty are valid. THE LIFETIME LIMITED WARRANTY STATED IN THIS TECHNICAL DATA SHEET IS EXCLUSIVE OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, NONE OF WHICH SHALL APPLY TO THE PRODUCT. TO THE MAXIMUM EXTENT PERMITTED UNDER THE LAW OF THE JURISDICTION WHERE THE PRODUCT IS SOLD, THIS WARRANTY ALSO EXCLUDES LIABILITY FOR ANY LOSS OF PROFITS, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY LIFETIME LIMITED WARRANTY ON THE PRODUCTS. LICK NORTH AMERICA SHALL NOT BE LIABLE FOR ANY LOSS, CLAIM, EXPENSE OR DAMAGE CAUSED BY, CONTRIBUTED TO OR ARISING OUT OF THE ACTS OR OMISSIONS OF OWNER OR THIRD PARTIES, WHETHER NEGLIGENT OR OTHERWISE. IN NO EVENT SHALL LICK NORTH AMERICA 'S LIABILITY UNDER ANY CAUSE OF ACTION WHATSOEVER EXCEED THE COST OF THE PRODUCT GIVING RISE TO THE CLAIM, WHETHER BASED IN CONTRACT, WARRANTY, INDEMNITY OR TORT (INCLUDING NEGLIGENCE AND STRICT LIABILITY) OR OTHERWISE.

SAFETY DATA SHEET

1. Identification

Product identifier Lick North America – Matt Paint
Recommended use Architectural Coating
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Lick North America
Address 10685 – B Hazelhurst Dr. .
31849 Houston TX 77043
Email hello@lickhome.com

Telephone +18449922969

Emergency telephone CHEMTREC: 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1
Carcinogenicity (inhalation) Category 2
Reproductive toxicity Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. May cause cancer by inhalation. Suspected of damaging fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	< 22
Kaolin	1332-58-7	< 5
Limestone	1317-65-3	< 5

Chemical name	CAS number	%
Aluminum hydroxide	21645-51-2	< 2
Amorphous Silica: Uncalcinated Diatomaceous Earth	61790-53-2	< 2
Silicon dioxide, crystalline silica-free	7631-86-9	< 2
Trimethylolpropane	77-99-6	< 0.2
2-Methyl-2H-isothiazol-3-one	2682-20-4	< 0.1
3-Iodo-2-propynyl butyl carbamate	55406-53-6	< 0.1
5-Chloro-2-methyl-2H-isothiazol-3-one	26172-55-4	< 0.1

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (l).

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

Components

Type

Value

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

TWA

80 mg/m³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components

Type

Value

Form

Kaolin (CAS 1332-58-7)

PEL

5 mg/m³

Respirable fraction.

15 mg/m³

Total dust.

Limestone (CAS 1317-65-3)

PEL

5 mg/m³

Respirable fraction.

15 mg/m³

Total dust.

Titanium dioxide (CAS 13463-67-7)

PEL

15 mg/m³

Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components

Type

Value

Form

Amorphous Silica:
Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

TWA

0.8 mg/m³

Kaolin (CAS 1332-58-7)

TWA

20 mppcf

5 mg/m³

Respirable fraction.

15 mg/m³

Total dust.

50 mppcf

Total dust.

15 mppcf

Respirable fraction.

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

TWA

20 mppcf

US. ACGIH Threshold Limit Values

Components

Type

Value

Form

Aluminum hydroxide (CAS 21645-51-2)

TWA

1 mg/m³

Respirable fraction.

Kaolin (CAS 1332-58-7)

TWA

2 mg/m³

Respirable fraction.

Titanium dioxide (CAS 13463-67-7)

TWA

10 mg/m³

US. NIOSH: Pocket Guide to Chemical Hazards

Components

Type

Value

Form

Amorphous Silica:
Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

REL

6 mg/m³

Kaolin (CAS 1332-58-7)

TWA

6 mg/m³

TWA

5 mg/m³

Respirable.

10 mg/m³

Total

Limestone (CAS 1317-65-3)

TWA

5 mg/m³

Respirable.

10 mg/m³

Total

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

TWA

6 mg/m³

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Milky white to colored liquid.
Physical state	Liquid.
Form	Liquid.
Color	Various.
Odor	Slightly ammoniacal.
Odor threshold	Not available.
pH	7 - 10
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	< 1 (n-BuAc=1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	> 1 (Air=1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Moderately soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.

Oxidizing properties Not oxidizing.
VOC 1.75 - 2.82 g/L

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability Material is stable under normal conditions.
Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.
Conditions to avoid Contact with incompatible materials.
Incompatible materials Strong oxidizing agents. Strong acids.
Hazardous decomposition products Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Suspected of causing cancer by inhalation. Prolonged inhalation may be harmful.
Skin contact May cause an allergic skin reaction.
Eye contact Direct contact with eyes may cause temporary irritation.
Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Aluminum hydroxide (CAS 21645-51-2)		
Acute		
Oral LD50	Rat	> 5000 mg/kg
Kaolin (CAS 1332-58-7)		
Acute		
Dermal LD50	Rat	> 5000 mg/kg
Inhalation LC50	Rat	> 2 mg/l, 4 Hours
Oral LD50	Rat	> 5000 mg/kg
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)		
Acute		
Dermal LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation <i>Dust</i> LC50	Rat	> 0.14 mg/l, 4 Hours
Oral LD50	Rat	> 3300 mg/kg
Titanium dioxide (CAS 13463-67-7)		
Acute		
Oral LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)	3 Not classifiable as to carcinogenicity to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Kaolin (CAS 1332-58-7)		
Aquatic		
<i>Acute</i>		
Crustacea	LC50	Daphnia magna
		> 1.1 g/l, 48 Hours
Titanium dioxide (CAS 13463-67-7)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna
		> 100 mg/l, 48 Hours
Fish	LL50	Oryzias latipes
		> 100 mg/l, 96 Hours

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	The product is water soluble and may spread in water systems.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4)	1.0 % One-Time Export Notification only.
5-Chloro-2-methyl-2H-isothiazol-3-one (CAS 26172-55-4)	1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) All components on the TSCA 8(b) inventory are designated "active" or are exempt from reporting under the Inventory Update Rule.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Respiratory or skin sensitization
Carcinogenicity
Reproductive toxicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations

US. Massachusetts RTK - Substance List

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)
Kaolin (CAS 1332-58-7)
Limestone (CAS 1317-65-3)
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)
Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

3-Iodo-2-propynyl butyl carbamate (CAS 55406-53-6)
Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)
Kaolin (CAS 1332-58-7)
Limestone (CAS 1317-65-3)
Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)
Kaolin (CAS 1332-58-7)
Limestone (CAS 1317-65-3)
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)
Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)
Kaolin (CAS 1332-58-7)
Limestone (CAS 1317-65-3)
Titanium dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988
Acetaldehyde (CAS 75-07-0)	Listed: April 1, 1988
Ethylene oxide (CAS 75-21-8)	Listed: July 1, 1987
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988
Methyloxirane (CAS 75-56-9)	Listed: October 1, 1988
Silica, Crystalline (airborne particles of respirable size) (CAS 14808-60-7)	Listed: October 1, 1988
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009
------------------------------	------------------------

California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8)	Listed: February 27, 1987
------------------------------	---------------------------

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009
------------------------------	------------------------

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Titanium dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	21-April-2021
Revision date	-
Version #	01
HMIS® ratings	Health: 2* Flammability: 1 Physical hazard: 0

Disclaimer Lick North America Inc cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

SAFETY DATA SHEET

1. Identification

Product identifier Lick North America Inc – Eggshell Paint

Recommended use Architectural Coating, Interior.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Lick North America Inc.
Address 10685 – B Hazelhurst Dr.
31849 Houston TX 77043
Email Hello@lickhome.com
Telephone +18449922969
Emergency telephone CHEMTREC: 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1
Carcinogenicity (inhalation) Category 2
Reproductive toxicity Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. Suspected of causing cancer by inhalation. Suspected of damaging fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	< 20
Kaolin	1332-58-7	< 5
Aluminum hydroxide	21645-51-2	< 2

Chemical name	CAS number	%
Silicon dioxide, crystalline silica-free	7631-86-9	< 2
Trimethylolpropane	77-99-6	< 1
2-Methyl-2H-isothiazol-3-one	2682-20-4	< 0.1
5-Chloro-2-methyl-2H-isothiazol-3-one	26172-55-4	< 0.1

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (l).

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
--------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA Components

Components	Type	Value
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	80 mg/m ³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	20 mppcf	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum hydroxide (CAS 21645-51-2)	TWA	1 mg/m ³	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	6 mg/m ³	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Milky white to colored liquid.
Physical state	Liquid.
Form	Liquid.
Color	Various.
Odor	Slightly ammoniacal.

Odor threshold Not available.

pH 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point Not available.

Evaporation rate < 1 (n-BuAc=1)

Flammability (solid, gas) Not applicable.

Vapor pressure Not available.

Vapor density > 1 (Air=1)

Relative density Not available.

Solubility(ies)

Solubility (water) Moderately soluble

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

VOC 0.868 - 1.967 g/L

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition products Carbon oxides. Metal oxides.

11. Toxicological information**Information on likely routes of exposure**

Inhalation Suspected of causing cancer by inhalation. Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
-------------------	----------------	---------------------

Aluminum hydroxide (CAS 21645-51-2)

Acute

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Kaolin (CAS 1332-58-7)

Acute

Dermal

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Inhalation

LC50	Rat	> 2 mg/l, 4 Hours
------	-----	-------------------

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Acute

Dermal

LD50	Rabbit	> 5000 mg/kg, 24 Hours
------	--------	------------------------

Inhalation

Dust

LC50	Rat	> 0.14 mg/l, 4 Hours
------	-----	----------------------

Oral

LD50	Rat	> 3300 mg/kg
------	-----	--------------

Titanium dioxide (CAS 13463-67-7)

Acute

Oral

LD50	Rat	> 5000 mg/kg
------	-----	--------------

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer by inhalation.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Kaolin (CAS 1332-58-7)			
Aquatic			
<i>Acute</i>			
Crustacea	LC50	Daphnia magna	> 1.1 g/l, 48 Hours
Titanium dioxide (CAS 13463-67-7)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	> 100 mg/l, 48 Hours
Fish	LL50	Oryzias latipes	> 100 mg/l, 96 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil The product is water soluble and may spread in water systems.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

5-Chloro-2-methyl-2H-isothiazol-3-one (CAS 26172-55-4) Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

1.0 % One-Time Export Notification only.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components on the TSCA 8(b) inventory are designated "active" or are exempt from reporting under the Inventory Update Rule.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical

Yes
Classified hazard categories Respiratory or skin sensitization
 Carcinogenicity
 Reproductive toxicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations**US. Massachusetts RTK - Substance List**

Kaolin (CAS 1332-58-7)
 Silicon dioxide, crystalline silica-free (CAS 7631-86-9)
 Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Kaolin (CAS 1332-58-7)
 Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Kaolin (CAS 1332-58-7)
 Silicon dioxide, crystalline silica-free (CAS 7631-86-9)
 Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Kaolin (CAS 1332-58-7)
 Titanium dioxide (CAS 13463-67-7)

California Proposition 65

WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988
Acetaldehyde (CAS 75-07-0)	Listed: April 1, 1988
Crystalline silica (airborne particles of respirable size) (CAS 14808-60-7)	Listed: October 1, 1988
Ethylene oxide (CAS 75-21-8)	Listed: July 1, 1987
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988
Methyloxirane (CAS 75-56-9)	Listed: October 1, 1988
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009
------------------------------	------------------------

California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8)	Listed: February 27, 1987
------------------------------	---------------------------

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009
------------------------------	------------------------

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 14-July-2021

Revision date -

Version # 01

HMIS® ratings Health: 2*
Flammability: 1
Physical hazard: 0

Disclaimer Lick North America Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.